



## AA 3300X SERIES POU Water Cooler Specification Sheet

### Cabinet

Cold-rolled 20 gauge embossed steel with baked on acrylic enamel finish.

### Drip tray

Lift out design, which can be connected to mains drainage. High impact durable plastic. Removable anti splash grid.

### Taps

Push type. Made of high impact durable ABS.  
Easy to remove and clean.

### Cup Holder

Integrated cup holder with exposed locking nuts to open up for easy refilling of cups.  
(Available on floor standing models only)

### Removable lower front panel

Spring loaded lower front panel. Remove drip tray and simply press down to remove entire lower front panel for easy access.

### Refrigeration System

Quiet, air cooled static-type condenser. No fan required. Protected against motor overload.  
Unit hermetically sealed. R-134a refrigerant.

### Cooling System

Stainless steel 3 Litre cold water tank.  
Thermostatically controlled from 4-12 degrees Celsius.

### Heating System

Stainless Steel 2 Litre tank. 430 watt instantaneous heating. Bi-metal temperature control. Designed to prevent total drainage for heating element protection. Easily accessible hot water tank drain at the back of cooler.

### Power supply

220 Volt, 50/60Hz. 3 pin plug and 180 cm power cord.

### Dimensions

Floor standing: H 117.5cm x W 34cm x D 34cm  
Benchtop: H 47cm x W 34cm x D 34cm



For further information contact



08000 682 820